



No. 30 ASTM 4869

4444 Hunt St. Pryor, OK 74361
Email: info@gaproofing.us
Phone: 918-825-5200
Fax: 918-825-5207

Company Website: GAProofing.us
Dealer Support: GAPdealers.com



WE OWN THE PAPER MILL

LOWER PRICING.
LOWER LEAD TIMES.
HIGHER QUALITY RAW MATERIALS.

No. 30 ASTM 4869

PRODUCT DESCRIPTION

GAP No. 30 ASTM 4869 is a underlayment product that is manufactured from superior quality organic felt that is saturated with asphalt

PRODUCT USE

GAP 30 ASTM 4869 underlayment is applied over the roofing deck before installation of asphalt shingles. This product is highly recommended as an underlayment for architectural shingles and is not recommended for 20 year 3 tab shingles.

TECHNICAL DATA

ASTM D 4869 Type 1

Width of Roll	36"
Roof Coverage per Roll	216 sq ft
Mass of Saturated Felt Roll	13.0 lbs/ 100 ft sq
Mass of Saturant	6.0 lbs / 100 ft sq
Mass of Desaturated Felt	5.0 lbs / 100 ft sq
Saturation by Weight (min)	110%
Saturation Efficiency (min) by Weight	75%
Breaking Strength at 77F (min)	
Machine Direction	30 lbf/in
Cross Direction	15 lbf/in
Pass 4 Hour Liquid Transmission Water Test	YES
Pliability at 77F when bend 90 degrees	1/2" radius

Pallet Size 42" X 42" No. of Rolls per Pallet = 30

MANUFACTURING LOCATIONS:

Pryor, OK

McGregor, TX

Shafter, CA

Jasper, FL