



GAP No. 30 Jumbo Split Felt

4444 Hunt St. Pryor, OK 74361
Email: info@gaproofing.us
Phone: 918-825-5200
Fax: 918-825-5207

Company Website: GAProofing.us
Dealer Support: GAPdealers.com



WE OWN THE PAPER MILL

*LOWER PRICING.
LOWER LEAD TIMES.
HIGHER QUALITY RAW MATERIALS.*

GAP No. 30 Jumbo Split Felt

PRODUCT DESCRIPTION

GAP No.30 Jumbo Split felt is a 18" underlayment product that is manufactured from superior quality organic felt that is saturated with asphalt

PRODUCT USE

GAP No.30 Jumbo 18" Split underlayment is applied over the roofing deck before installation of wood shake shingles

TECHNICAL DATA

Available in ASTM D 226 Type II and ASTM 4869 Type II

SPEC. FOR ASTM D 226

Width of Roll	18"
Roof Coverage per Roll	180 sq ft
Mass of Saturated Felt Roll	23.4 lbs/ 100 ft sq
Mass of Saturant	11.0 lbs / 100 ft sq

ASTM D 4869 TYPE 1

Width of Roll	18"
Roof Coverage per Roll	180 sq ft
Mass of Saturated Felt Roll	18.0 lbs/ 100 ft sq
Mass of Asphalt Saturant	10.0 lbs / 100 ft sq

Pallet Size 42" X 42" No. of Rolls per Pallet =69

MANUFACTURING LOCATIONS:

Pryor, OK