



Pro 30

GAP Roofing, Inc.
4444 Hunt Street
Pryor, OK 74361

Phone: 918-825-5200
FAX: 918-825-5207

Company Website: GAProofing.us
Dealer Support: GAPdealers.com



WE OWN THE PAPER MILL

LOWER PRICING.
LOWER LEAD TIMES.
HIGHER QUALITY RAW MATERIALS.

Pro 30

PRODUCT DESCRIPTION

GAP Pro30 is an underlayment product that is manufactured from superior organic felt and is saturated with asphalt.

PRODUCT USE

GAP Pro 30 underlayment is applied over the roofing deck before installation of asphalt shingles. This product is highly recommended as an underlayment for architectural shingles and is not recommended for 20 year 3 tab shingles.

TECHNICAL DATA

Exceeds requirements for ASTM D 4869 Type 1

Width of Roll	36"
Roof Coverage per Roll	216 sq ft
Mass of Saturated Felt Roll	18.0 lbs/ 100 ft sq
Mass of Asphalt Saturant	10.0 lbs / 100 ft sq
Mass of Desaturated Felt	6.0 lbs / 100 ft sq
Saturation by Weight (min)	120%
Saturation efficiency (min) by weight	70%
Breaking Strength at 77F (min)	
Machine direction	30 lbf/in
Cross Direction	15 lbf/in
Pass 4 hour liquid Transmission water test	YES
Pliability at 77F when bend 90 degrees	1/2" radius

Pallet Size 42" X 42" No. of Rolls per Pallet = 30

MANUFACTURING LOCATIONS:

Pryor, OK