



TILE UNDERLAYMENT

GAP Roofing, Inc.
4444 Hunt Street
Pryor, OK 74361

Phone: 918-825-5200
FAX: 918-825-5207

Company Website: GAProofing.us
Dealer Support: GAPdealers.com



WE OWN THE PAPER MILL

LOWER PRICING.
LOWER LEAD TIMES.
HIGHER QUALITY RAW MATERIALS.

TILE UNDERLAYMENT

PRODUCT DESCRIPTION

GAP Tile Underlayment product that is manufactured from superior quality organic felt that is saturated with asphalt and then coated on both sides with weathering grade coating asphalt and then covered on top with opaque head lap granules.

PRODUCT USE

GAP Tile Underlayment is applied over the roofing deck before installation of concrete tiles.

TECHNICAL DATA

ASTM D 6380 M Type II

Width of Roll	36"
Roof coverage per Roll	108 Square feet
Mass of coated roll	80.3 lbs/ 100 sq. ft
Mass of granule portion	71.5 lbs/ 100 sq. ft
Mass of desaturated felt	9.0 lbs/ 100 sq. ft
Asphalt Saturation	150%
Mass of weather side coating and mineral (filler)	18.5 lbs/ 100 sq. ft
Mass of granules	24.0 lbs/ 100 sq. ft
Maximum weight of displaced granules	1.0 gm.

Pallet Size 42" X 48" No of Rolls per Pallet = 25

MANUFACTURING LOCATIONS:

Pryor, OK