



4444 Hunt St. Pryor, OK 74361
Email: info@gaproofing.us
Phone: 918-825-5200
Fax: 918-825-5207

Company Website: GAProofing.us
Dealer Support: GAPdealers.com

15 "G" Felt



WE OWN THE PAPER MILL

LOWER PRICING.
LOWER LEAD TIMES.
HIGHER QUALITY RAW MATERIALS.

15 "G" Felt

PRODUCT DESCRIPTION

G 15 roofing felt is an economical roofing underlayment product that is manufactured from organic felt and is saturated with asphalt

PRODUCT USE

"G"15 felt is an underlayment is applied over the roofing deck before installation of asphalt shingles. This is recommended for use with 20 year asphalt shingles.

TECHNICAL DATA

This product is sold as is and is not ASTM rated.

Width of Roll	36"
Roof Coverage per Roll	432 sq ft
Mass of Saturated Felt Roll	8.0 lbs/ 100 ft sq
Mass of Asphalt Saturant	4.0 lbs / 100 ft sq
Mass of Desaturated Felt	4.0 lbs / 100 ft sq
Saturation by Weight (min)	80%

Pallet Size 40" X 40" No. of Rolls per Pallet = 35

MANUFACTURING LOCATIONS:

Pryor, OK

McGregor, TX

Shafter, CA

Jasper, FL