



4444 Hunt St. Pryor, OK 74361
Email: info@gaproofing.us
Phone: 918-825-5200
Fax: 918-825-5207

Company Website: GAProofing.us
Dealer Support: GAPdealers.com

GAP Pro 15



WE OWN THE PAPER MILL

*LOWER PRICING.
LOWER LEAD TIMES.
HIGHER QUALITY RAW MATERIALS.*

GAP Pro 15

PRODUCT DESCRIPTION

GAP Pro15 is an underlayment product that is manufactured from organic felt and is saturated with asphalt

PRODUCT USE

GAP Pro15 underlayment is applied over the roofing deck before installation of asphalt

TECHNICAL DATA

EXCEEDS Requirements for ASTM D 4869 Type 1

Width of Roll	36"
Roof Coverage per Roll	432 sq ft
Mass of Saturated felt roll	9.25 lbs/ 100 ft sq
Mass of Asphalt Saturant	5.0 lbs / 100 ft sq
Mass of Desaturated Felt	4.2 lbs / 100 ft sq
Saturation by Weight (min)	110%
Saturation Efficiency (min) by Weight	75%
Breaking Strength at 77F (min)	
Machine Direction	30 lbf/in
Cross Direction	15 lbf/in
Pass 4 Hour Liquid Transmission Water Test	YES
Pliability at 77F When Bend 90 Degrees	1/2" radius

Pallet Size 42" X 42" No. of Rolls per Pallet = 30

MANUFACTURING LOCATIONS:

Pryor, OK