



FIBERGLASS BASE SHEET G2

GAP Roofing, Inc.
4444 Hunt Street
Pryor, OK 74361

Phone: 918-825-5200
FAX: 918-825-5207

Company Website: GAProofing.us
Dealer Support: GAPdealers.com



WE OWN THE PAPER MILL

LOWER PRICING.
LOWER LEAD TIMES.
HIGHER QUALITY RAW MATERIALS.

FIBERGLASS BASE SHEET G2

PRODUCT DESCRIPTION

GAP Fiberglass Base G2 sheet is manufactured from tough inorganic Fiberglass mat then coated on both sides with weathering grade coating asphalt and then covered on top with white sand fines to prevent sticking in the roll.

PRODUCT USE

GAP Fiberglass base sheet is applied over the flat roofing deck or insulation as a Base Sheet by Mechanical Fasteners or Hot Asphalt before the application of Build-Up Roofing systems. This sheet is suitable as a vapor retarder, with a solid mopping of asphaltic material, under roof insulation or between multiple layers of insulation.

TECHNICAL DATA

ASTM D 4601-04 TYPE II

| | |
|--|--------------------------------|
| Width of Roll | 36" |
| Roof coverage per Roll | 324 sq ft 3 squares per roll |
| Roll Weight | 72 lbs |
| Mass of desaturated glass mat | 1.55 lbs / 100 ft sq |
| Mass of Base Sheet | 37.0 lbs / 100 ft sq |
| Mass of stabilizer and surfacing (Max) | 70% |
| Mass of asphalt coating (Min) | 5.6 lbs / 100 ft sq |
| Breaking Strength at 77F (min) | |
| Machine direction and Cross Direction | 22 lbf/in |
| Pliability, (1/2") Radius Maximum Failures | 0 |

Pallet Size 42" X 48" No of Rolls per Pallet = 20

MANUFACTURING LOCATIONS:

Pryor, OK