



ORGANIC BASE SHEET

GAP Roofing, Inc.
4444 Hunt Street
Pryor, OK 74361

Phone: 918-825-5200
FAX: 918-825-5207

Company Website: GAProofing.us
Dealer Support: GAPdealers.com



WE OWN THE PAPER MILL

LOWER PRICING.
LOWER LEAD TIMES.
HIGHER QUALITY RAW MATERIALS.

ORGANIC BASE SHEET

PRODUCT DESCRIPTION

GAP Organic Base sheet is manufactured from superior quality felt that is saturated with asphalt and then coated on both sides with weathering grade coating asphalt and then covered on top with mineral surface fines to prevent sticking in the roll.

PRODUCT USE

GAP organic base sheet is applied over the flat roofing deck or insulation before the application of Build-Up Roofing systems.

TECHNICAL DATA

ASTM 2626 04

Width of Roll	36"
Roof coverage per Roll=	216 sq ft
Mass of Base Sheet	37.0 lbs/ 100 ft sq
Mass of Asphalt Saturant	7.2 lbs / 100 ft sq
Mass of desaturated felt	5.2 lbs / 100 ft sq
Mass of Coating and surfacing (min)	18.0 lbs / 100 ft sq
Mass per side of asphalt coating (back coating)	3.5 lbs / 100 ft sq
Saturation efficiency (min) by weight	100%
Breaking Strength at 77F (min)	70%
Machine direction	35 lbf/in
Cross Direction	20 lbf/in
Water Vapor Permeance	0.3 grains/ hr. ft sq (in. Hg)1/2" radius

Pallet Size 42" X 48" No of Rolls per Pallet = 25

MANUFACTURING LOCATIONS:

Pryor, OK