



RAIN AND ICE PROTECTION

RAIN AND ICE PROTECTION INSTALLATION INSTRUCTIONS

PREPARATION

Sweep roof deck to remove dirt and debris. The roof deck must be clean, smooth and free of moisture. If moisture is present it will limit or inhibit adhesion.

On re-roofing, remove all old material from roof deck area to be covered

WEATHER CONDITIONS

Apply when air temperature is over 40F (5C) but below 100F (38C). If applied in temperatures below 40F GAP Rain and Ice is stiffer and will not fully seal until it is warmed. If applied in temperatures above 100F (38C), it may become difficult to remove the release poly backing.

If this situation should occur, move product to shaded area until cool. Once cooled, the release poly backing can be easily removed.

INSTALLATION

Rain and Ice is applied directly to the surface of the roof deck. See carton for complete instructions and precautions

COLD WEATHER INSTALLATIONS:

Mechanically fasten membrane to position until it has bonded to the roof deck.

FOR EXTERIOR USE ONLY

COVERAGE

1.95 SQ Roll Approximately 195 SF

PACKAGING

1.95 SQ Roll 36/Pallet

MANUFACTURING LOCATIONS:

Pryor, OK

LIMITATIONS

- Should not be applied over shingles or underlayment of any sort
 - Should not be applied over damp surfaces
 - Should not be left exposed to sunlight for more than 30 days (less if extreme heat conditions exist)
- CAUTION!!** Surface can be slippery if wet or covered with frost properties

PROPERTIES

Approximately Roll Weight: 1.95 Square 50 lbs

Membrane Width:

Membrane: 36"
Release: 37.5"

Membrane Length: 1.95 Square Roll 65 Feet

Membrane Thickness: 48 - 50 Mils

Application Method: Self Adhering

Surface Composition: Granules

Membrane Reinforcement: Fiberglass Mat

Backing Material: Silicone Coated Release Film

**FOR FURTHER SAFETY INFORMATION...
SEE MSDS REGARDING THIS PRODUCT.**