

GAP WaterGuard Self-Adhered Cap Sheet

SBS Modified Granulated Roll Roofing

Product Description

GAP WaterGuard Self-Adhered Cap Sheet is a unique SBS modified granulated, fiberglass (also available with polyester) reinforced roll roofing surface membrane. Available in a 4" or 19" selvedge areas, available in 9 colors and SBS coating with a fire-retardant stabilizer. The overall thickness is 111 mil nominal (ASTM D1777), 39 3/8" (width) x 34' (length), 1 square roll, weight approximately 78 lb. per roll, and shrink bagged for easy storage and handling.



Features and Benefits

- ✓ **Long lasting lower-slope Roofing** – *granulated exterior low-slope roofing with the ease of "self-adhered" installation...no messy adhesion issues*
- ✓ **Fast and easy self-adhered**– *unique bitumen modified formulation has a wide temperature install range and easy-to-use split release liner*
- ✓ **Highly pliable fiberglass mat reinforcement or polyester reinforcement** – *both reinforcement options available; offering strong material stability and conforms easily to valleys, corners and angles*
- ✓ **Exterior UV exposure** – *designed for direct exterior application and exposure*
- ✓ **Made in the USA** – *assured performance, safe components and US quality standards (no coal tar!)*
- ✓ **1 square roll available** – *easy to install, handle and eliminate waste/loss with better roll planning.*

Key Technical Details

Data (ASTM Specification D1970)

| | |
|------------------------|----------------------------|
| Rolls/Pallet | 25 |
| Weight/Roll | 78 lbs (nominal) |
| Width | 39 3/8" |
| Length | 34' |
| Thickness (ASTM D1777) | 110 Mils (nominal) |
| Coverage | 1 Square (111 square Feet) |

Additional ratings (ASTM Specification D1970)

| | |
|--|-----------------|
| _Perm Rating | <0.1 U.S. perms |
| Maximum Load MD/CD, (min 25 lbf/in) | Pass |
| Elongation @ break, (min. 10%) | Pass |
| Adhesion to plywood, min at 40°F 2.0 lbf/ft width | Pass |
| Adhesion to plywood, min at 75°F 12.0 lbf/ft width | Pass |
| Flexibility temperature -20° F | Pass |
| Tear Resistance MD/CD, (min 20 lbf) | Pass |
| Moisture Vapor Permeance | 0.1 U.S. perms |
| Seal ability around nail | No leaks, Pass |
| Waterproof integrity after low temp flexibility | No leaks, Pass |
| Waterproof integrity of lap seam | No leaks, Pass |
| Packaging | Shrink Bag |
| Manufacturing Location | U.S.A. |



**Roofing runs
in our blood!**

Still Family founded owned after 3 generations!

Note: We believe that the above statements are reliable and should be used for general guidance purposes only and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for purpose. There is no warrant of fitness for a purpose. Our standard terms and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products or publications. These data should not be considered a specification.

GAP Roofing Inc., 4444 Hunt Street, Pryor, OK 74361 (918) 825-5200