

GAP WaterGuard Self-Adhered Rain & Ice

SBS Modified “Fine” Granulated Underlayment (no Selvedge Edge!)

Product Description

GAP WaterGuard Self-Adhered Rain & Ice is a SBS modified “Fine” granulated, fiberglass reinforced roofing underlayment. Ideal for economical roofing offering great wind-uplift properties, eve, valley and ice damming protection. Unique walkable surface that bonds to itself, so no selvedge required. The overall thickness is 55 mils nominal (ASTM D1777), 36” (width) x 65’ (length), 2 square roll, weight approximately 60 lb. per roll, and shrink bagged for easy storage and handling.



Features and Benefits

- ✓ **Unique “fine” granulated surface** – *greater feeling of safety and security while walking, PLUS no selvedge edge required...it bonds to itself!*
- ✓ **Exceptional SBS rubberized adhesive backing** – *unique bitumen modified formulation with a wide temperature install range and great nail seal ability*
- ✓ **Highly pliable fiberglass mat reinforcement** – *conforms easily to valleys, corners and angles*
- ✓ **90-day UV exposure** – *longer dry-in time and greater protection from temporary exposure*
- ✓ **Meets ASTM D1970 testing and the 40+mil thickness** – *no concerns with code enforcement and significant “body” for assured performance and feel*
- ✓ **Made in the USA** – *assured performance, safe components and US quality standards (no coal tar!)*
- ✓ **1 & 2 square rolls available** – *easy to install, handle and eliminate waste/loss with better roll planning.*
- ✓ **Split Release liner** – *easy to install and repositioning*

Key Technical Details

Meets and exceeds ASTM D1970, **FBC# FL 22853.2**

Data (ASTM Specification D1970)

Rolls/Pallet	28
Weight/Roll	60 lbs (nominal)
Width	36”
Length	65’
Thickness (ASTM D1777)	55 Mils (nominal)
Coverage	2 Square (195 square Feet)

Additional ratings (ASTM Specification D1970)

_Perm Rating	<0.1 U.S. perms
Maximum Load MD/CD, (min 25 lbf/in)	Pass
Elongation @ break, (min. 10%)	Pass
Adhesion to plywood, min at 40°F 2.0 lbf/ft width	Pass
Adhesion to plywood, min at 75°F 12.0 lbf/ft width	Pass
Flexibility temperature - 20° F	Pass
Tear Resistance MD/CD, (min 20 lbf)	Pass
Moisture Vapor Permeance	0.1 U.S. perms
Seal ability around nail	No leaks, Pass
Waterproof integrity after low temp flexibility	No leaks, Pass
Waterproof integrity of lap seam	No leaks, Pass
Packaging	Shrink Bag
Manufacturing Location	U.S.A.



**Roofing runs
in our blood!**

Still Family founded owned after 3 generations!

Note: We believe that the above statements are reliable and should be used for general guidance purposes only and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for purpose. There is no warrant of fitness for a purpose. Our standard terms and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products or publications. These data should not be considered a specification.

GAP Roofing Inc., 4444 Hunt Street, Pryor, OK 74361 (918) 825-5200